

STREAMER X

The Streamer X is a professional video capture card, audio interface and control surface integrated in one compact device, making creating that looks and sounds incredible easy. It features studio-grade audio inputs for XLR microphones and instruments, headsets and RØDE Series IV wireless microphones, with an ultra-low-noise, high-gain Revolution Preamp™ and powerful APHEX® audio processing delivering pristine sound quality. HDMI connections offer up to 4K30 streaming and 4K60 pass-through for incredible video quality in a wide range of applications, from streaming and gaming, to podcasting and content creation, to business presentations. Variable Refresh Rate (VRR) support ensures smooth gaming without lag or screen tearing and two USB-C connections allow for easy integration with dual PC setups. Four fully customisable SMART pads allow for on-the-fly triggering of sound or voice FX, keyboard shortcuts and other actions on a computer for unmatched flexibility. It is also fully compatible with RØDE software, including UNIFY and RØDE Central for easy configuration and access to advanced features.

- Professional audio interface, video capture card and control surface integrated in one compact, easy-to-use device
- Up to 4K30 video capture and 4K60 pass-through via HDMI
- Variable Refresh Rate (VRR) support
- Neutrik® combo jack for connecting XLR microphones or instruments, with an ultra-low-noise, high-gain Revolution Preamp™ for pristine audio quality
- 3.5mm TRRS input for connecting headsets and 1/4-inch headphone output for zero-latency monitoring
- Integrated wireless receiver for connecting RØDE Series IV wireless microphones, including the Wireless GO II and Wireless ME
- Internal DSP for advanced audio processing powered by APHEX®
- Four fully customisable SMART pads for triggering sounds, voice effects and keyboards shortcuts or other actions on a computer
- Dual USB-C interfaces for connecting to two computers or mobile devices
- Easy configuration and control via RØDE Central desktop companion app
- Compatible with free UNIFY streaming software for advanced audio routing, mixing and configuration
- Designed and made in RØDE's precision manufacturing facilities in Sydney, Australia



ACOUSTIC, VIDEO & ELECTRICAL SPECIFICATIONS

Video Input Connectors:	1 x HDMI Type A 2.0
Video Passthrough Output:	1 x HDMI Type A 2.0
Max Input Resolutions (HDMI In):	4K60 HDR 1440p144 HDR 1080p240 HDR
Variable Refresh Rate Support (VRR):	Yes
Max Capture Resolutions:	4K30 1440p60 1080p120 1080p60 HDR
Audio Input Connectors:	1 x XLR Combo Jack (Mic/Instrument) 1 x Wireless Receiver 1 x Input HDMI
Audio Output Connectors:	1 x 3.5 TRRS Headset Jack (I/O) 1 x 1/4" Headphone Jack
Input Dynamic Range:	113dB
Preamp Noise:	-131.5dBV (A-weighted)
Frequency Range:	Microphone Inputs: 20Hz-20kHz Headphone Output: 20Hz-20kHz
Microphone Input Impedance (Ω):	4KΩ
Instrument Input Impedance (Ω):	1MΩ



SMART PADS



4K30 CAPTURE



4K60 HDR
PASSTHROUGH



MIC, WIRELESS &
HEADSET INPUTS

ACOUSTIC, VIDEO & ELECTRICAL SPECIFICATIONS CONT.

Preamplifier Gain Range:	76dB
Phantom Power:	Yes
Direct Monitor:	Yes
Headphone Output Power:	125mW per channel
Internal Storage (GB):	2GB (SMART Pads)
Power Requirements:	Via USB: 5V @ 3A

MECHANICAL SPECIFICATIONS

Weight (grams):	380g
Dimensions (millimetres):	Length: 144mm Width: 122mm Height: 51mm
Included Accessories:	1 x Streamer X 1 x SC27 1 x Power Adapter
RØDE Software Compatibility:	RØDE Central RØDE Unify

DIGITAL SPECIFICATIONS

USB Interface:	USB 1: USB 3.1 type C USB 2: USB 2.0 type C
Bit Depth:	24-bit
Sampling Rate (kHz):	48kHz
Processing:	APHEX Processing RØDE Voice FX
Minimum OS Requirements:	macOS 10.15 or later Windows 10 Version 1803 or later Windows 11

WHATS IN THE BOX



DIMENSIONS

